



Butylon is a double-sided tape for sealing nail penetrations through underlays as well as sealing underlays, air barriers or vapour control layers (AVCL's) to both smooth and rough surfaces. Both internal and external use.

Product features & benefits

- Double-sided tape
- Ideal for creating airtight seals around nail penetrations through underlays/AVCL's or adhering underlays/AVCL's to both smooth & rough surfaces
- Highly durable
- Watertight

Area of application

Suitable for:

- Adhering underlays & vapour control layers/air barriers to smooth & rough surfaces
- Use below tile battens or counterbattens to seal nail penetrations through the underlay
- Both internal & external use

Material

Double-sided butylon-rubber adhesive

Dimensions

20mm x 25m
50mm x 25m

Packaging (rolls/carton)

4 rolls per carton (20mm x 25m)
2 rolls per carton (50mm x 25m)

Product codes

KU 0103 (20mm x 25m)
KU 0104 (50mm x 25m)



TECHNICAL DATA

Adhesive	Butyl
Solvent	Solvent free
Installation temperature	> +5°C
Temperature stability	-40 to + 80°C
UV stability	4 months
Resistance to ageing	It remains permanently elastic & adhesive
Shelf life	2 years ≤ 20°C

TS-09#16-EN-0912. Für Druckfehler wird keine Haftung übernommen. ®Eingetragenes Warenzeichen der Klüber GmbH.